



"INOTEC" STANDARDIZATION LINE "Inotec" Standardization line:

2 x "Inotec" Twin shaft paddle mixer 2000L

Type IPM 2000

- all stainless steel

- twin shaft paddle mixer
- intermeshing mixer
- useful content : 1.600 L
- dimensions (L x w x h) : ± 4.100 x 1.500 x 2.700 mm
- 1 front discharge guard
- with weighing cells
- 18 kW

+

2 x Outfeed conveyor belt"

Type IFB 1300/800

- all stainless steel
- comes under the discharge guards of the mixer
- plastic belt
- 0,7 kW
- outfeed height ± 1.200 mm in a eurobin / Dolav

+

2 x Loader for eurobins

Type IHV 2000-300

- all stainless steel
- for 200L or 300 L eurobins
- dimensions: (L x W x H): ± 900 x 1.300 x 4.020 mm
- 1,6 kW

+

Elevating spiral screw with infeed belt

Elevating spiral screw

Type IFS 5600/400

- all stainless steel
- mobile
- 5.3 kW
- screw diameter 400 mm
- Loading height 800 mm
- Unloading height 3.200 mm
- dimensions: (L x W x H): ± 5.200 x 2.500 x 4.450mm

+

Infeed belt

- all stainless steel
- white pvc belt
- belt width 700 mm
- belt length 2.500 mm

- Unloading height 2.800 mm

+

control box

Type IPL 05-02-N

- Total 58 kW
- 3x 400V -50Hz 98A
- Year of construction 2003
- dimensions: (lxwxh) : ± 1,800 x 550 x 1,800 mm
- PLC control system Siemens S7-300 + Simatic panel OP270

+

inspection platform

Interested? Contact us!

phone: +32 56 77 33 50 - email: info@barsso.com